

Bench-Top
Steam Sterilizers

Medium Steam
Sterilizers

Large Steam
Sterilizers

Medical
Waste Solutions

Clean Steam
Generators

■ MEDIUM STEAM STERILIZERS

Azteca AC Series



- Round chamber – from 75 up to 200 liters.
- Focused design – the 75 liters unit fits exactly 1 STU.
- Easy to use – one touch operation.
- Fast and economical – sterilization cycles from 21 minutes with advanced water and energy saving systems.
- Best solution – for hospitals, medical centers and as secondary sterilizers for emergency cases at Operating Theaters.

Distributor:



DELTA PLUS (PVT) LTD.

H # 220, STREET # 13
Khayaban-E-Kashmir
G-15/4, Islamabad , Pakistan
TEL+92(51)2160155-6
FAX: +92(51)2160157
info@deltapluspvt.com
URL: www.deltapluspvt.com



celitron
WE THINK GREEN!

Celitron Medical Technologies Kft.

Address: H-2600 Vác, Szent László str. 36. Hungary
Telephone: +36 27 412-610, Fax: +36 27 412-611
Web: www.celitron.com
E-mail: info@celitron.com

Advanced Bio Waste Treatment

ISO9001 and ISO 13485 certified company with CE certified products

Azteca AC Series

The Azteca AC Sterilizer family consists of pre- and post-vacuum sterilizers designed with the highest quality for sterilization of wrapped or unwrapped goods such as fabrics, surgical instruments, utensils, and other heat and moisture stable materials. With their capacity from 75 up to 200 liters they cover a large field of applications for hospitals, medical centers and Operating Theaters.

The Azteca AC Sterilizers use steam under pressure as the sterilizing agent at temperatures ranging from 121°C to 134°C. The units are standard equipped with internal steam generators to enable faster cycles with a low energy consumption, and eliminate the dependence on an external steam source and its steam quality.

The vessel is a heated jacketed round chamber, made of corrosion-resistant stainless steel 316L. The highly efficient, high-quality Hanno-Tech insulation material releases no particles; hence the Azteca AC Sterilizers can be used under cleanroom conditions. The advanced insulation technology further contributes to the high energy efficiency of the units.

A microprocessor based control system; state of the art Freescale technology automatically controls all operations. The system includes a digital color touch-screen LCD display, communication, self and remote diagnosis and PC connection for external documentation and printing, ensuring a reliable, safe and user-friendly operation. The displayed information is available for users in a variety of languages.



SPECIFICATIONS:

Model Azteca AC Series	AC-450	AC-450 Premium	AC-470*	AC-470 Premium*	AC-575*	AC-5100
Chamber dimensions, Inner Dia. x Depth	400 x 670 mm		400 x 750 mm		500 x 700 mm	500 x 1000 mm
Chamber volume	75 l		90 l		150 l	200 l
External dimensions W x H x D	750 x 630 x 970 mm				850 x 730 x 1050 mm	850 x 730 x 1300 mm
Approximate Weight	160 kg		170 kg		200 kg	240 kg
Power supply**	3 ph. 380-400 V, 50/60 Hz					
Power with steam generator	7 kW	6,1 kW	9,9 kW	9 kW	12 kW	
Available sterilization cycles	Flash 134°C/Unwrapped 134°C/Wrapped 134°C/Prion 134°C/Porous 121°C					
Available test cycles	Bowie & Dick test / Vacuum test					
Touch-screen display	LCD 5.7" Color Graphic					
Cabinet	Painted quality steel	Stainless steel	Painted quality steel	Stainless steel		

* Models with two doors are available
 ** Adjustable to different voltage systems